



795SS, 895SS

and 790SS Hot Water Pressure Washers

North America's #1 Brand
of High-Pressure Cleaning Equipment

Electric / Belt Drive



Heater coil carries
a 5-year warranty

Pressure relief valve protects
the machine and user
from thermal expansion

Upright, oil fired burner delivers high efficiency
with diesel fuel, kerosene or home-heating oil

Control panel includes adjustable temperature
control plus heavy-duty heater and pump motor
switches

5 HP, 230V, 1PH Baldor electric
motor (Model 795SS) comes with
thermal overload protection and
manual reset



High quality float valve
helps maintain constant
pressure and flow and traps
sediment or debris.
It is recessed at center
of chassis for protection
and balance



Rugged belt drive
provides smooth,
quiet operation and
outstanding reliability

Ground Fault Circuit
Interrupter (GFCI breaker)
provides additional protection
against shock hazard

Rust-proof cross
linked polyethylene
fuel tank eliminates
condensation that can
contaminate fuel. Fuel
gauge in cap.

Hotsy-designed
Triplex pumps
carry a 7-year
limited warranty

Model 795SS
3.5 GPM @2000 PSI



Convenient hose-reel bracket
accepts swivel or stationary reels

Pneumatic tires with inner tubes
provide easy maneuverability over
pavement or rough terrain

Belt tension adjusts easily
by turning a single bolt

Variable upstream detergent
injection ensures high-pressure
sudsing



Model 895SS
3.5 GPM
@3000 PSI

FEATURES

- 2.8 or 3.5 GPM @ 2000 or 3000 PSI
- Oil Fired Burners
- 208V or 230V, 1PH
- 4 to 8.2 HP
- 1330 or 1490 RPM Belt Drive Pumps



Built-in wand
and nozzle holders
provide convenient
storage

www.Hotsy.com

Nothing Cleans Like a Hotsy!

795SS, 895SS and 790SS Hot-Water ELECTRIC Models

■ Oil Fired Burners ■ 2.8 or 3.5 GPM @ 2000 or 3000 PSI ■ Hotsy 7-Year Pump Warranty

Designed for tough, industrial cleaning.

SPECIFICATIONS

BELT DRIVE

MODEL	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	HOSE	SHIP WT
790SS	3.0	2000	4TEFC*	230/1	20	Oil	289,900	HHC340R.1	Belt	Std	50'	450
795SS	3.5	2000	5	230/1	24	Oil	289,900	HHC340R.1	Belt	Std	50'	455
795SS-208	3.5	2000	5	208/1	27	Oil	289,900	HHC340R.1	Belt	Std	50'	500
895SS	3.5	3000	8.2	230/1	36	Oil	289,900	HHC506R.1	Belt	Std	50'	480

Dimensions: 37"l x 28"w x 45.5"h

*Totally enclosed fan cooled (TEFC)

DON'T FORGET THE SOAP!

Hotsy pressure washers clean best when matched with specially formulated Hotsy detergents. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. All are highly concentrated, so a little goes a long way.



HOTSY SOLUTION SELECTOR
What's the best detergent for your next job? Find out with our solution selector. Scan this QR code or visit HOTSY.com

AVAILABLE OPTIONS

- 8" Oil-Fired Draft Dampener

SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.



PARTS & ACCESSORIES

Your local Hotsy dealer would be happy to provide an onsite demonstration to determine which pressure washer accessories will help speed cleaning and lower your costs. Hotsy dealers stock thousands of pressure washer replacement parts such as high pressure hose, trigger guns, high pressure nozzles, pumps, engines, motors, unloaders, filters and wands. In addition, you'll find a number of accessories designed to speed cleaning, the most common accessories are telescoping wands, pivot and non-pivot hose reels, flat surface cleaners and high pressure turbo nozzles.



FIND OUT MORE ONLINE: HOTSY.COM

Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631
www.Hotsy.com email: info@Hotsy.com
P/N 8.914-210.0 Effective 3/16



Specifications & product descriptions subject to change without notice.
Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.
A member of KÄRCHER North America ©2016 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at $\pm 10\%$ and in some cases are tighter within $\pm 5\%$ of listed specifications.